
NSN 5320-01-414-4976

Pin-rivet - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand** Identification Code Color: Violet, purple Fastener Length: Between 1.440 inches and 1.460 inches Head Style: Straight pan **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.079 inches and 0.080 inches Shank Diameter: Between 0.188 inches and 0.189 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.357 inches and 0.377 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp Grip Length: Between 1.120 inches and 1.130 inches Min. Tensile Strength (psi): 3180 pounds per square inch **Thread Size:** 0.190 inches Shear Strength: 5300 double pounds per square inch Material: Steel comp 4130 **Material Specification:** Mil-s-5626 military specification single material response Surface Treatment: Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

NSN 5320-01-414-4976

Pin-rivet - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A528u0

Mil-std (military Standard):

Mil-s-5626 spec.

