

View Online at <https://aerobasegroup.com/nsn/5320-01-414-5055>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.302 inches and 1.322 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.0635 inches and 0.0645 inches

Shank Diameter:

Between 0.1625 inches and 0.1635 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.3256 inches and 0.3304 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 0.995 inches and 1.005 inches

Min. Tensile Strength (psi):

2180 pounds per square inch

Thread Size:

0.164 inches

Shear Strength:

4010 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

5 size must be installed with a torque controlled hex key

Material:

Titanium alloy uns r56400

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear spec. 294, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjc

Specification Data:

73197-hl13 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0