NSN 5320-01-414-5690

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-5690 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.065 inches and 1.985 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2172 inches and 0.2182 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.370 inches and 0.390 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.745 inches and 0.755 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.188 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi kote 1, aluminum coating 294 per hi-shear mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-414-5690

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0