NSN 5320-01-414-5718

View Online at https://aerobasegroup.com/nsn/5320-01-414-5718

Pin-rivet - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Fastener Length: Between 2.052 inches and 2.072 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.063 inches and 0.064 inches **Shank Diameter:** Between 0.162 inches and 0.163 inches **Shank Style: Head Major Diameter:** Between 0.256 inches and 0.261 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.745 inches and 1.755 inches Min. Tensile Strength (psi): 1290 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** 5 size must be installed using a torque controlled hex key. Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5320-01-414-5718

Pin-rivet - Page 2 of 2



| _ | | •• | • • | | | | |
|----|----|----|-----|-----|-----|---|----|
| וו | em | ш | 112 | rız | 211 | n | ٠. |
| | | | | | | | |

No

Fiig:

A528u0