# NSN 5320-01-414-6574

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 2.040 inches and 2.050 inches

#### Head Style:

Err-090

#### **Head Height:**

Between 0.130 inches and 0.140 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3735 inches and 0.3745 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.530 inches and 0.600 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 1.495 inches and 1.505 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

## Thread Size:

0.375 inches

#### Shear Strength:

95000 single pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Hi kote 1, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# NSN 5320-01-414-6574

Pin-rivet - Page 2 of 2

Demilitarization:

No

Fiig:

A528u0

