## NSN 5320-01-414-7173

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7173 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.815 inches and 1.835 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2172 inches and 0.2182 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.370 inches and 0.390 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.495 inches and 1.505 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.188 inches Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi kote 1, aluminum coating 294 per hi-shear mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-414-7173

Pin-rivet - Page 2 of 2



Fiig:

A528u0