

View Online at <https://aerobasegroup.com/nsn/5320-01-414-7190>

Thread Class:

3a

Thread Direction:

Right-hand

Identification Code Color:

Black

Fastener Length:

Between 1.865 inches and 1.885 inches

Head Style:

Flush countersunk

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.370 inches and 1.380 inches

Min. Tensile Strength (psi):

9200 pounds per square inch

Thread Size:

0.312 inches

Shear Strength:

14600 double pounds per square inch

Countersink Angle:

100.0 degrees

Special Features:

M73197-h113

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-shear spec.294, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Specification Data:

73197-hl13 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0