NSN 5320-01-414-7196

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7196

view Online at https://aerobasegroup.com/hsh/3520-01-414-7130
Thread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Black
Fastener Length:
Between 2.740 inches and 2.760 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.1270 inches and 0.1295 inches
Shank Diameter:
Between 0.3110 inches and 0.3120 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.6287 inches and 0.6335 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 2.245 inches and 2.255 inches
Min. Tensile Strength (psi):
9200 pounds per square inch
Thread Size:
0.312 inches
Countersink Angle:
100.0 degrees
Material:
Titanium alloy uns r56400
Material Specification:
Ams4967 assn standard single material response or ams4928 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-shear spec.294, cage 73197 mfr ref single treatment response
Thread Series Designator:
Unjf
Specification Data:
73197-hl13 manufacturers standard
Shelf Life:
N/a

NSN 5320-01-414-7196

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0