# NSN 5320-01-414-7213

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7213

**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

3.885 inches

## Head Style:

Err-090

#### Head Height:

Between 0.150 inches and 0.160 inches

## Width Between Flats:

Between 0.1895 inches and 0.1930 inches

#### Shank Diameter:

Between 0.4677 inches and 0.4682 inches

#### Shank Style:

## Head Major Diameter:

Between 0.615 inches and 0.650 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

3.250 inches

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### **Thread Size:**

0.438 inches

## Material:

Titanium alloy

## **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

## Surface Treatment:

Aluminum

## Surface Treatment Specification:

Hi-kote no 1, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5320-01-414-7213

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

