NSN 5320-01-414-7219

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7219 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.505 inches and 1.515 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1895 inches and 0.1920 inches **Shank Diameter:** Between 0.4260 inches and 0.4310 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.592 inches and 0.676 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.870 inches and 0.880 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.437 inches **Special Features:** Threads are color coded black. Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi kote 1, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-414-7219

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0