NSN 5320-01-414-7544

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7544

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.940 inches and 1.960 inches

Head Style:

Err-090

Head Height:

Between 0.064 inches and 0.074 inches

Width Between Flats:

Between 0.0791 inches and 0.0806 inches

Shank Diameter:

Between 0.2016 inches and 0.2026 inches

Shank Style:

Head Major Diameter:

Between 0.357 inches and 0.377 inches

Grip Length:

Between 1.620 inches and 1.630 inches

Min. Tensile Strength (psi):

3180 pounds per square inch

Thread Size:

0.190 inches

Shear Strength:

6130 double pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-414-7544

Pin-rivet - Page 2 of 2

Fiig: A528u0

