## NSN 5320-01-414-7570

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7570 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.010 inches and 1.030 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2641 inches and 0.2651 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.415 inches and 0.440 inches **Grip Length:** Between 0.615 inches and 0.635 inches Min. Tensile Strength (psi): 5820 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 10490 double pounds per square inch **Special Features:** Color black on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5320-01-414-7570

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0