NSN 5320-01-414-7585

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7585

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

2.185 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.5302 inches and 0.5307 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.740 inches and 0.775 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

1.500 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.500 inches

Material:

Titanium alloy

Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi-kote no. 1, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-414-7585

Pin-rivet - Page 2 of 2

Fiig: A528u0

