

View Online at <https://aerobasegroup.com/nsn/5320-01-414-7589>

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.130 inches and 2.140 inches

Head Style:

Err-090

Head Height:

Between 0.150 inches and 0.160 inches

Width Between Flats:

Between 0.1895 inches and 0.1920 inches

Shank Diameter:

Between 0.4260 inches and 0.4310 inches

Shank Style:

Pin-riquet, straight, threaded

Head Major Diameter:

Between 0.592 inches and 0.676 inches

Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

Grip Length:

Between 1.495 inches and 1.505 inches

Min. Tensile Strength (psi):

160000 pounds per square inch

Thread Size:

0.437 inches

Shear Strength:

95000 single pounds per square inch

Special Features:

Threads are color coded black.

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Hi kote 1, cagec 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A528u0