NSN 5320-01-414-7592

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-7592 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: 2.560 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.5302 inches and 0.5307 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.740 inches and 0.775 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** 1.875 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote no 1, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-414-7592

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0