NSN 5320-01-414-9030

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-9030 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.745 inches and 1.765 inches **Head Style:** Err-090 **Head Height:** Between 0.020 inches and 0.030 inches Width Between Flats: Between 1.270 inches and 1.295 inches **Shank Diameter:** Between 0.3422 inches and 0.3432 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.490 inches and 0.520 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.245 inches and 1.255 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.313 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1, aluminum coating 294 per hi-shear mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

NSN 5320-01-414-9030

Pin-rivet - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A528u0