NSN 5320-01-414-9032

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-9032 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.365 inches and 1.385 inches **Head Style:** Err-090 **Head Height:** Between 0.020 inches and 0.030 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3422 inches and 0.3432 inches **Shank Style: Head Major Diameter:** Between 0.490 inches and 0.520 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.870 inches and 0.880 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.313 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi kote 1, aluminum coating 294 per hi-shear mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-414-9032

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0