

View Online at <https://aerobasegroup.com/nsn/5320-01-414-9064>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 1.510 inches and 1.530 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.080 inches and 0.090 inches

**Width Between Flats:**

Between 0.0947 inches and 0.0967 inches

**Shank Diameter:**

Between 0.2641 inches and 0.2651 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.415 inches and 0.440 inches

**Grip Length:**

Between 1.120 inches and 1.130 inches

**Min. Tensile Strength (psi):**

5820 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

10490 double pounds per square inch

**Special Features:**

Color black on thread end

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment Specification:**

Cagec 73197, specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0