# NSN 5320-01-414-9112

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-414-9112

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 3.130 inches and 3.140 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.150 inches and 0.160 inches

#### Width Between Flats:

Between 0.1895 inches and 0.1920 inches

#### Shank Diameter:

Between 0.4260 inches and 0.4310 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.592 inches and 0.676 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 2.495 inches and 2.505 inches

### Min. Tensile Strength (psi):

160000 pounds per square inch

#### Thread Size:

0.437 inches

#### Shear Strength:

95000 single pounds per square inch

# **Special Features:**

Threads are color coded black.

#### Material:

Titanium alloy uns r56400

# Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

# Surface Treatment:

Aluminum

# Surface Treatment Specification:

Hi kote 1, cagec 73197 mfr ref single treatment response

# Thread Series Designator:

Unjf

#### Shelf Life:

N/a



# NSN 5320-01-414-9112

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

