# NSN 5320-01-414-9696

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-414-9696



# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 0.660 inches and 0.700 inches

### Head Style:

Err-090

#### Head Height:

Between 0.042 inches and 0.050 inches

# Width Between Flats:

Between 0.0791 inches and 0.0806 inches

# Shank Diameter:

Between 0.1885 inches and 0.1895 inches

#### Shank Style:

Pin-rivet, straight, threaded

### Head Major Diameter:

Between 0.298 inches and 0.312 inches

# **End Application:**

Pacer dawn

# Grip Length:

Between 0.313 inches and 0.375 inches

# Thready Qty Per Inch (tpi):

32

# Thread Size:

0.190 inches

# Shear Strength:

156000 single pounds per square inch

# Material:

Steel comp h11

# **Material Specification:**

Ams 6485 assn standard single material response or ams 6487 assn standard single material response

#### Surface Treatment:

Nickel and cadmium

# Surface Treatment Specification:

Ams 2416 assn standard single treatment response

# **Thread Series Designator:**

Unjf

# **Specification Data:**

80205-nas4450 professional/industrial association standard

# Shelf Life:

N/a

# NSN 5320-01-414-9696

Pin-rivet - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A528u0

