NSN 5320-01-414-9696

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-414-9696

View Online at https://aerobasegroup.com/nsn/5320-01-414-9696
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.660 inches and 0.700 inches
Head Style:
Err-090
Head Height:
Between 0.042 inches and 0.050 inches
Width Between Flats:
Between 0.0791 inches and 0.0806 inches
Shank Diameter:
Between 0.1885 inches and 0.1895 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.298 inches and 0.312 inches
End Application:
Pacer dawn
Grip Length:
Between 0.313 inches and 0.375 inches
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Shear Strength:
156000 single pounds per square inch
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams 6487 assn standard single material response
Surface Treatment:
Nickel and cadmium
Surface Treatment Specification:
Ams 2416 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas4450 professional/industrial association standard
Shelf Life:

N/a

NSN 5320-01-414-9696

Pin-rivet - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A528u0