

View Online at <https://aerobasegroup.com/nsn/5320-01-415-0026>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

1.000 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1270 inches and 0.1295 inches

**Shank Diameter:**

Between 0.3427 inches and 0.3432 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.6287 inches and 0.6335 inches

**Lubrication:**

Cetyl alcohol, specification 305, hi-shear corp

**Grip Length:**

0.500 inches

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Thread Size:**

0.250 inches

**Shear Strength:**

95000 single pounds per square inch

**Countersink Angle:**

100.0 degrees

**Material:**

Titanium alloy

**Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

**Surface Treatment:**

Aluminum alloy

**Surface Treatment Specification:**

Hi-kote no. 1, caged 73197 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0