
# NSN 5320-01-415-0033

Pin-rivet - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

1.375 inches

#### Head Style:

Flush countersunk

# Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3427 inches and 0.3432 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

#### Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

0.875 inches

# Min. Tensile Strength (psi):

160000 pounds per square inch

# Thread Size:

0.312 inches

#### Shear Strength:

95000 single pounds per square inch

#### **Countersink Angle:**

100.0 degrees

#### Material:

Titanium alloy

#### Material Specification:

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum alloy

#### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 5320-01-415-0033

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

