NSN 5320-01-415-0673



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-415-0673 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.065 inches and 2.085 inches **Head Style:** Err-090 **Head Height:** Between 0.064 inches and 0.074 inches Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.357 inches and 0.377 inches **Grip Length:** Between 1.745 inches and 1.755 inches Min. Tensile Strength (psi): 3180 pounds per square inch **Thread Size:** 0.190 inches **Shear Strength:** 6130 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-415-0673

Pin-rivet - Page 2 of 2



Fiig:

A528u0