NSN 5320-01-415-0708

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-0708 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.240 inches and 2.260 inches **Head Style:** Err-090 **Head Height:** Between 0.102 inches and 0.112 inches Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3266 inches and 0.3276 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.472 inches and 0.505 inches **Grip Length:** Between 1.745 inches and 1.755 inches Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 16000 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-415-0708

Pin-rivet - Page 2 of 2



Fiig:

A528u0