## NSN 5320-01-415-0710

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-415-0710



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

#### Fastener Length:

Between 2.490 inches and 2.510 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.102 inches and 0.112 inches

#### Width Between Flats:

Between 0.1270 inches and 0.1295 inches

#### Shank Diameter:

Between 0.3266 inches and 0.3276 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.472 inches and 0.505 inches

#### Grip Length:

Between 1.995 inches and 2.005 inches

#### Min. Tensile Strength (psi):

9200 pounds per square inch

#### Thread Size:

0.3125 inches

#### Shear Strength:

16000 double pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

#### Thread Series Designator:

Unjf

### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-415-0710

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

