NSN 5320-01-415-0713

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-415-0713



Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 1.990 inches and 2.010 inches

Head Style:

Err-090

Head Height:

Between 0.102 inches and 0.112 inches

Width Between Flats:

Between 0.1270 inches and 0.1295 inches

Shank Diameter:

Between 0.3266 inches and 0.3276 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.472 inches and 0.505 inches

Grip Length:

Between 1.495 inches and 1.505 inches

Min. Tensile Strength (psi):

9200 pounds per square inch

Thread Size:

0.3125 inches

Shear Strength:

16000 double pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5320-01-415-0713

Pin-rivet - Page 2 of 2

Fiig: A528u0

