## NSN 5320-01-415-0724

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Identification Code Color:

Black

#### Fastener Length:

Between 1.155 inches and 1.175 inches

#### **Head Style:**

Flush countersunk

#### Width Between Flats:

Between 0.1895 inches and 0.1930 inches

#### Shank Diameter:

Between 0.4829 inches and 0.4839 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.7088 inches and 0.7148 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

#### Grip Length:

Between 0.495 inches and 0.505 inches

### Thread Size:

0.438 inches

#### **Countersink Angle:**

100.0 degrees

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5320-01-415-0724

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

