
# NSN 5320-01-415-0727

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Identification Code Color:

Black

#### Fastener Length:

Between 3.655 inches and 3.675 inches

#### **Head Style:**

Flush countersunk

## Width Between Flats:

Between 0.1895 inches and 0.1930 inches

#### Shank Diameter:

Between 0.4829 inches and 0.4839 inches

#### Shank Style:

Pin-rivet, straight, threaded

## Head Major Diameter:

Between 0.7088 inches and 0.7148 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 2.995 inches and 3.005 inches

## Thread Size:

0.438 inches

#### **Countersink Angle:**

100.0 degrees

## Material:

Iron alloy 660

## **Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

# NSN 5320-01-415-0727

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

