NSN 5320-01-415-0735

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-0735 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.660 inches and 1.680 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3891 inches and 0.3901 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.530 inches and 0.600 inches **Grip Length:** Between 1.120 inches and 1.130 inches Min. Tensile Strength (psi): 14000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 22700 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-415-0735

Pin-rivet - Page 2 of 2



Fiig:

A528u0