
## NSN 5320-01-415-0738

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

Between 1.285 inches and 1.305 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.130 inches and 0.140 inches

#### Width Between Flats:

Between 0.1582 inches and 0.1617 inches

#### Shank Diameter:

Between 0.3891 inches and 0.3901 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.530 inches and 0.600 inches

#### Grip Length:

Between 0.745 inches and 0.755 inches

## Min. Tensile Strength (psi):

14000 pounds per square inch

## Thread Size:

0.375 inches

#### Shear Strength:

22700 double pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

#### Thread Series Designator:

Unjf

## Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-01-415-0738

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

