NSN 5320-01-415-0756

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-0756 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 2.290 inches and 2.300 inches **Head Style:** Err-090 **Head Height:** Between 0.130 inches and 0.140 inches Width Between Flats: Between 0.1582 inches and 0.1617 inches **Shank Diameter:** Between 0.3735 inches and 0.3745 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.530 inches and 0.600 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.745 inches and 1.755 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.375 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi kote 1, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

Unit Of Measure:

NSN 5320-01-415-0756

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0