NSN 5320-01-415-1252

Pin-rivet - Page 1 of 2

Thread Class:

Right-hand

Yellow

Thread Direction:

Fastener Length:

Identification Code Color:

Between 1.910 inches and 1.930 inches

За



View Online at https://aerobasegroup.com/nsn/5320-01-415-1252

Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches Shank Diameter: Between 0.3266 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf	Head Style:
Between 0.1270 inches and 0.1295 inches Shank Diameter: Between 0.3266 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification single treatment response Thread Series Designator:	Flush countersunk
Shank Diameter: Between 0.3266 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification single treatment response Thread Series Designator:	Width Between Flats:
Between 0.3266 inches and 0.3276 inches Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Between 0.1270 inches and 0.1295 inches
Shank Style: Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Shank Diameter:
Pin-rivet, straight, threaded Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Between 0.3266 inches and 0.3276 inches
Head Major Diameter: Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Shank Style:
Between 0.6287 inches and 0.6335 inches Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Pin-rivet, straight, threaded
Lubrication: Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Head Major Diameter:
Cetyl alcohol Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Between 0.6287 inches and 0.6335 inches
Grip Length: Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Lubrication:
Between 1.370 inches and 1.380 inches Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Cetyl alcohol
Min. Tensile Strength (psi): 12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Grip Length:
12300 pounds per square inch Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Between 1.370 inches and 1.380 inches
Thread Size: 0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Min. Tensile Strength (psi):
0.312 inches Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	12300 pounds per square inch
Shear Strength: 19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Thread Size:
19160 double pounds per square inch Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	0.312 inches
Countersink Angle: 100.0 degrees Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Shear Strength:
Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	19160 double pounds per square inch
Special Features: Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Countersink Angle:
Powder blast top of head, with color yellow thread end Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	100.0 degrees
Material: Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Special Features:
Nickel alloy 718 Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Powder blast top of head, with color yellow thread end
Material Specification: Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Material:
Ams 5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Nickel alloy 718
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Material Specification:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Ams 5662 assn standard single material response
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:	Surface Treatment:
Qq-p-35 federal specification single treatment response Thread Series Designator:	Passivate
Thread Series Designator:	Surface Treatment Specification:
	Qq-p-35 federal specification single treatment response
Unjf	Thread Series Designator:
	Unjf

NSN 5320-01-415-1252

Pin-rivet - Page 2 of 2



Specification Data	Spe	ecifica	ition	Data:
--------------------	-----	---------	-------	-------

76823-03a063 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0