NSN 5320-01-415-1362

Pin-rivet - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5320-01-415-1362

inread Class:
3a
Thread Direction:
Right-hand
Identification Code Color:
Black
Fastener Length:
Between 1.760 inches and 1.780 inches
Head Style:
Flush countersunk
Width Between Flats:
Between 0.0947 inches and 0.0967 inches
Shank Diameter:
Between 0.2641 inches and 0.2651 inches
Shank Style:
Pin-rivet, straight, threaded
Head Major Diameter:
Between 0.3898 inches and 0.3948 inches
Lubrication:
Cetyl alcohol, specification 305, hi-shear corp
Grip Length:
Between 1.370 inches and 1.380 inches
Min. Tensile Strength (psi):
3700 pounds per square inch
Thread Size:
0.250 inches
Shear Strength:
10490 double pounds per square inch
Countersink Angle:
100.0 degrees
Special Features:
1/64" oversize.
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response or ams4967 assn standard single material response
Surface Treatment:
Aluminum
Surface Treatment Specification:
Hi-shear spec.294, cage 73197 mfr ref single treatment response
Thread Series Designator:
Unjf

NSN 5320-01-415-1362

Pin-rivet - Page 2 of 2



S	pe	cif	ic	ati	on	D	ata	:

73197-hl111 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0