NSN 5320-01-415-1367

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-1367 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Black **Fastener Length:** Between 1.510 inches and 1.530 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2641 inches and 0.2651 inches **Shank Style: Head Major Diameter:** Between 0.3898 inches and 0.3948 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.120 inches and 1.130 inches Min. Tensile Strength (psi): 3700 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 10490 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** 1/64" oversize. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:**

Aluminum

Surface Treatment Specification:

Hi-shear spec.294, cage 73197 mfr ref single treatment response

Thread Series Designator:

Unjf

NSN 5320-01-415-1367

Pin-rivet - Page 2 of 2



Specific	cation	Data:
----------	--------	-------

73197-hl111 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A528u0