NSN 5320-01-415-1966

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-1966 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.385 inches and 1.405 inches **Head Style:** Err-090 **Head Height:** Between 0.015 inches and 0.025 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2797 inches and 0.2807 inches **Shank Style: Head Major Diameter:** Between 0.435 inches and 0.460 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.995 inches and 1.005 inches Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 95000 single pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Hi-kote 1 aluminum coating 294 per hi-shear mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5320-01-415-1966

Pin-rivet - Page 2 of 2



Demilitarization:

No

Fiig:

A528u0