
## NSN 5320-01-415-2004

Pin-rivet - Page 1 of 2





#### **Thread Class:**

3a

**Thread Direction:** 

Right-hand

#### Fastener Length:

Between 3.125 inches and 3.145 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.150 inches and 0.160 inches

#### Width Between Flats:

Between 0.1895 inches and 0.1930 inches

#### Shank Diameter:

Between 0.4516 inches and 0.4526 inches

#### Shank Style:

Pin-rivet, straight, threaded

#### Head Major Diameter:

Between 0.592 inches and 0.676 inches

#### Grip Length:

Between 2.495 inches and 2.505 inches

#### Min. Tensile Strength (psi):

18900 pounds per square inch

#### Thread Size:

0.4375 inches

#### Shear Strength:

30600 double pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

#### **Thread Series Designator:**

Unjf

### Shelf Life:

N/a

#### Unit Of Measure:

--

#### Demilitarization:

No

# NSN 5320-01-415-2004

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

