NSN 5320-01-415-2746

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-2746 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.625 inches and 1.645 inches **Head Style:** Err-090 **Head Height:** Between 0.150 inches and 0.160 inches Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4516 inches and 0.4526 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.592 inches and 0.676 inches **Grip Length:** Between 0.995 inches and 1.005 inches Min. Tensile Strength (psi): 18900 pounds per square inch **Thread Size:** 0.4375 inches **Shear Strength:** 30600 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Ams 4928 assn standard single treatment response or ams 4967 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5320-01-415-2746

Pin-rivet - Page 2 of 2



Fiig:

A528u0