
# NSN 5320-01-415-2747

Pin-rivet - Page 1 of 2



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Fastener Length:

Between 2.425 inches and 2.445 inches

#### Head Style:

Err-090

#### Head Height:

Between 0.178 inches and 0.188 inches

#### Width Between Flats:

Between 0.2207 inches and 0.2242 inches

#### Shank Diameter:

Between 0.5141 inches and 0.5151 inches

#### Shank Style:

#### Head Major Diameter:

Between 0.717 inches and 0.770 inches

#### Grip Length:

Between 1.745 inches and 1.755 inches

### Min. Tensile Strength (psi):

25600 pounds per square inch

# Thread Size:

0.500 inches

#### Shear Strength:

39600 double pounds per square inch

#### Material:

Titanium alloy uns r56400

#### **Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

#### Surface Treatment:

Aluminum

#### Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

#### Thread Series Designator:

Unjf

# Shelf Life:

N/a

### Unit Of Measure:

--

# Demilitarization:

No



# NSN 5320-01-415-2747

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

