NSN 5320-01-415-2749

Pin-rivet - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5320-01-415-2749

Thread Class:

3a

Thread Direction:

Right-hand

Fastener Length:

Between 2.925 inches and 2.945 inches

Head Style:

Err-090

Head Height:

Between 0.178 inches and 0.188 inches

Width Between Flats:

Between 0.2207 inches and 0.2242 inches

Shank Diameter:

Between 0.5141 inches and 0.5151 inches

Shank Style:

Pin-rivet, straight, threaded

Head Major Diameter:

Between 0.717 inches and 0.770 inches

Grip Length:

Between 2.245 inches and 2.255 inches

Min. Tensile Strength (psi):

25600 pounds per square inch

Thread Size:

0.500 inches

Shear Strength:

39600 double pounds per square inch

Material:

Titanium alloy uns r56400

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Cagec 73197, specification 294 mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No



NSN 5320-01-415-2749

Pin-rivet - Page 2 of 2

Fiig: A528u0

