

View Online at <https://aerobasegroup.com/nsn/5320-01-415-2750>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 3.425 inches and 3.445 inches

**Head Style:**

Err-090

**Head Height:**

Between 0.178 inches and 0.188 inches

**Width Between Flats:**

Between 0.2207 inches and 0.2242 inches

**Shank Diameter:**

Between 0.5141 inches and 0.5151 inches

**Shank Style:**

Pin-rivet, straight, threaded

**Head Major Diameter:**

Between 0.717 inches and 0.770 inches

**Grip Length:**

Between 2.745 inches and 2.755 inches

**Min. Tensile Strength (psi):**

25600 pounds per square inch

**Thread Size:**

0.500 inches

**Shear Strength:**

39600 double pounds per square inch

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Cagec 73197, specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0