
# NSN 5320-01-415-2765

Pin-rivet - Page 1 of 2



Thread Class:

3a

Thread Direction:

**Right-hand** 

## Identification Code Color:

Black

## Fastener Length:

Between 3.025 inches and 3.045 inches

#### **Head Style:**

Flush countersunk

## Width Between Flats:

Between 0.1270 inches and 0.1295 inches

## Shank Diameter:

Between 0.3579 inches and 0.3589 inches

#### Shank Style:

## Head Major Diameter:

Between 0.6287 inches and 0.6335 inches

## Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

## Grip Length:

Between 2.495 inches and 2.505 inches

## Thread Size:

0.312 inches

#### **Countersink Angle:**

100.0 degrees

## Material:

Iron alloy 660

## **Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

## **Thread Series Designator:**

Unjf

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No



# NSN 5320-01-415-2765

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

