## NSN 5320-01-415-3438

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-3438 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.690 inches and 1.710 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.0791 inches and 0.0806 inches **Shank Diameter:** Between 0.2016 inches and 0.2026 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.3765 inches and 0.3813 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.370 inches and 1.380 inches **Thread Size:** 0.3125 inches **Countersink Angle:** 100.0 degrees **Criticality Code Justification:** Feat **Special Features:** Weapon system essential Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4927 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294. Cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-415-3438

Pin-rivet - Page 2 of 2



| _   |     |      |     |       |            |    |
|-----|-----|------|-----|-------|------------|----|
| ם ו | mil | 11+2 | riz | 21 to | $\alpha$ r | ٠. |
| DС  |     | IILa | 114 | аи    | v          | ı. |

No

Fiig:

A528u0