## NSN 5320-01-415-3464

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-3464 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.925 inches and 1.945 inches **Head Style:** Err-090 **Head Height:** Between 0.178 inches and 0.188 inches Width Between Flats: Between 0.2207 inches and 0.2242 inches **Shank Diameter:** Between 0.5141 inches and 0.5151 inches **Shank Style: Head Major Diameter:** Between 0.717 inches and 0.770 inches **Grip Length:** Between 1.245 inches and 1.255 inches Min. Tensile Strength (psi): 25600 pounds per square inch **Thread Size:** 0.500 inches **Shear Strength:** 39600 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-415-3464

Pin-rivet - Page 2 of 2



Fiig:

A528u0