## NSN 5320-01-415-3474

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-3474 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.990 inches and 2.010 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1270 inches and 0.1295 inches **Shank Diameter:** Between 0.3266 inches and 0.3276 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.6287 inches and 0.6335 inches **Grip Length:** Between 1.495 inches and 1.505 inches Min. Tensile Strength (psi): 9200 pounds per square inch **Thread Size:** 0.3125 inches **Shear Strength:** 16000 double pounds per square inch **Countersink Angle:** 100.0 degrees **Special Features:** Color black on thread end Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Cagec 73197, specification 294 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5320-01-415-3474

Pin-rivet - Page 2 of 2



em			

No

Fiig:

A528u0