## NSN 5320-01-415-3482



Pin-rivet - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5320-01-415-3482 **Thread Class:** За **Thread Direction:** Right-hand **Identification Code Color:** Black **Fastener Length:** Between 1.155 inches and 1.175 inches **Head Style:** Flush countersunk Width Between Flats: Between 0.1895 inches and 0.1930 inches **Shank Diameter:** Between 0.4829 inches and 0.4839 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.8812 inches and 0.8884 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 0.495 inches and 0.505 inches **Thread Size:** 0.438 inches **Countersink Angle:** 100.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5737 assn standard single material response or ams 5731 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** 294, cagec 73197 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5320-01-415-3482

Pin-rivet - Page 2 of 2



Fiig:

A528u0