
# NSN 5320-01-415-3496

Pin-rivet - Page 1 of 2





# **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Identification Code Color:

Black

#### Fastener Length:

Between 1.955 inches and 1.975 inches

#### **Head Style:**

Flush countersunk

# Width Between Flats:

Between 0.2207 inches and 0.2242 inches

#### Shank Diameter:

Between 0.5454 inches and 0.5464 inches

#### Shank Style:

Pin-rivet, straight, threaded

# Head Major Diameter:

Between 1.0068 inches and 1.0139 inches

# Lubrication:

Cetyl alcohol, specification 305, hi-shear corp

# Grip Length:

Between 1.245 inches and 1.255 inches

# Thread Size:

0.500 inches

#### **Countersink Angle:**

100.0 degrees

# Material:

Iron alloy 660

# **Material Specification:**

Ams 5737 assn standard single material response or ams 5731 assn standard single material response

#### Surface Treatment:

Aluminum

# Surface Treatment Specification:

294, cagec 73197 mfr ref single treatment response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# NSN 5320-01-415-3496

Pin-rivet - Page 2 of 2

**Fiig:** A528u0

