## NSN 5320-01-415-4472

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-4472 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.197 inches and 1.217 inches **Head Style:** Err-090 **Head Height:** Between 0.080 inches and 0.090 inches Width Between Flats: Between 0.0947 inches and 0.0967 inches **Shank Diameter:** Between 0.2485 inches and 0.2495 inches **Shank Style: Head Major Diameter:** Between 0.415 inches and 0.440 inches Lubrication: Cetyl alcohol **End Application:** Pacer dawn **Grip Length:** 0.875 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Thread Size:** 0.250 inches **Shear Strength:** 

95000 single pounds per square inch

Material:

Titanium alloy

**Material Specification:** 

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:** 

Aluminum

**Surface Treatment Specification:** 

294, fsc-73197 mfr ref single treatment response

**Thread Series Designator:** 

Unjf

## NSN 5320-01-415-4472

Pin-rivet - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A528u0