

View Online at <https://aerobasegroup.com/nsn/5320-01-415-5400>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Fastener Length:**

Between 3.875 inches and 3.895 inches

**Head Style:**

Flush countersunk

**Width Between Flats:**

Between 0.1895 inches and 0.1930 inches

**Shank Diameter:**

Between 0.4516 inches and 0.4526 inches

**Shank Style:**

Pin-riquet, straight, threaded

**Head Major Diameter:**

Between 0.8812 inches and 0.8884 inches

**Grip Length:**

Between 3.245 inches and 3.255 inches

**Min. Tensile Strength (psi):**

18900 pounds per square inch

**Thread Size:**

0.4375 inches

**Shear Strength:**

30600 double pounds per square inch

**Countersink Angle:**

100.0 degrees

**Special Features:**

Color black on thread end

**Material:**

Titanium alloy uns r56400

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Cagec 73197, specification 294 mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A528u0