NSN 5320-01-415-5412

Pin-rivet - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5320-01-415-5412 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.427 inches and 1.447 inches **Head Style:** Err-090 **Head Height:** Between 0.055 inches and 0.065 inches Width Between Flats: Between 0.063 inches and 0.064 inches **Shank Diameter:** Between 0.162 inches and 0.163 inches **Shank Style:** Pin-rivet, straight, threaded **Head Major Diameter:** Between 0.306 inches and 0.322 inches Lubrication: Cetyl alcohol, specification 305, hi-shear corp **Grip Length:** Between 1.120 inches and 1.130 inches Min. Tensile Strength (psi): 2180 pounds per square inch **Thread Size:** 0.164 inches **Shear Strength:** 4010 double pounds per square inch Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response **Surface Treatment:** Aluminum **Thread Series Designator:** Unjc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5320-01-415-5412

Pin-rivet - Page 2 of 2



Fiig:

A528u0